



**Important** Please read supply and installations notes on back page. Specifications may change without prior notice. Do not scale.

# H2533

## 5.0 tonne 2 post symmetric electro-hydraulic with twin ram

### Features

- High version available - H2533H
- Fully electro-hydraulic giving long life and low cost
- Completely baseless with a clear floor area
- Electromechanical locking device in case of rope failure
- Automatic arm locking
- Anti-toe protection guards
- Single screw pads
- Overload safety-device
- Descent control valve
- Parachute valve
- "Dead man" controls 24V
- Electrically controlled mechanical safety device
- Mechanical synchronisation

### Technical data

- |                |  |
|----------------|--|
| Voltage        | 230-400v/50Hz - Three phase only   |
| Motor rating   | 2.2kW - 3ph  |
| Operation      | Electro-hydraulic  |
| Capacity       | 5000kg   |
| Weight         | 850kg  |
| Lift/lower     | 35 seconds   |
| Lifting height | 1935mm   |
| Pad height     | 100mm  |
| Pad extensions | 60mm 100mm 170mm   |
| Concrete       | 35N/mm <sup>2</sup> strength continuous slab<br>250 mm minimum thickness |
|                | Withstand 3.0 tonne static load  |
|                | Withstand 5.0 tonne shock load   |