

TLT235SB TLT240SB

Symmetric Floorplate 2-post Lift



TLT235SBA TLT240SBA

(TLTE32/E40SBA)

Symmetric Floorplate 2-post Lift



Model	TLT235SB Floor plate	TLT240SB Floor plate	TLT235SBA Floorplate	TLT240SBA Floorplate
Capacity	3.5T(7875lbs)	4.0T(9000lbs)	3.5T(7875lbs)	4.0T(9000lbs)
Lifting height	1950mm(76.8inch)	1950mm(76.8inch)	1950mm(76.8inch)	1950mm(76.8inch)
Lifting time	50Sec	50Sec	50Sec	50Sec
Lowering time	40Sec	40Sec	40Sec	40Sec
Power supply	AC380V 3PH 220V 1PH	AC380V 3PH 220V 1PH	AC380V 3PH 220V 1PH	AC380V 3PH 220V 1PH
Motor power	2.2kW	2.2kW	2.2kW	2.2kW
Passing width	2486mm (97.9inch)	2486mm (97.9inch)	2486mm (97.9inch)	2486mm (97.9inch)
Overall width	3370mm (132.7inch)	3370mm (132.7inch)	3370mm (132.7inch)	3370mm (132.7inch)
Overall height	2780mm(109.4inch)	2780mm(109.4inch)	2780mm(109.4inch)	2780mm(109.4inch)

Features (TLT235SB/TLT240SB)

- The cable and oil pipe are fully concealed, with decent and elegant appearance.
- Designed based on the international standard, meeting the demand of the garage and workshop.
- Top limit switch, effectively protecting the vehicle from overhead collision.
- Dual hydraulic cylinders drive, stable lifting and lowering.
- Automatic full-scope safety lock, safe and simple in operation.
- Adopt two steel cables for equalization, force two carriages to move synchronously, and effectively prevent the vehicle from tilting.
- Lowest height of lifting pad is 110mm, good for repairing low chassis or low profile car.

Features(TLT235SBA/TLT240SBA)

- The cable and oil pipe are fully concealed, with decent and elegant appearance.
- Designed based on the international standard, meeting the demand of the garage and workshop.
- Top limit switch, effectively protecting the vehicle from overhead collision.
- Dual hydraulic cylinders drive, stable lifting and lowering.
- Electromagnetic full-scope safety lock.
- Lowering electrically, safe and simple in operation.
- Adopt two steel cables for equalization, force two carriages to move synchronously, and effectively prevent the vehicle from tilting.
- Lowest height of lifting pad is 110mm, good for repairing low chassis or low profile car.